

# Data Sheet

We make sure



## SCENICVIEW E19-7 19 Inch LCD Display

Issue October 2007

Pages 2

An attractive price doesn't mean that you have to compromise on style or performance. Sleek and space-saving, the SCENICVIEW E19-7 is the best choice LCD. It offers best performance for the office and multimedia applications. It is the ideal LCD for those seeking to upgrade their bulky CRT with limited budget.

### Highlights

- Best performance to an affordable price
  - Office applications
  - Internet and multimedia are supported best
- Very easy and comfortable to use
  - Plug & Play
  - Auto-adjust
  - Easy-to-use OSD menu

### Ergonomics

- Optimum flicker-free and distortion-free ergonomics
- Excellent color purity
- Well balanced brightness uniformity
- Excellent high contrast 800:1
- Space saving design

### Technical highlights

- 19" (48cm) LCD Display
- Excellent contrast 800:1
- Brightness 300 cd/m<sup>2</sup>
- Fast response time (typ.) 5ms

### Reliability

- Low power consumption (EPA 'On Mode' 25 W)
- Power management according to EPA
- Guaranteed quality and stability



<b>Visible screen diagonal</b>	19 inch (48 cm)
<b>Resolution</b>	
Pixels	1280 x 1024
Pixels*	1024 x 768
Pixels*	800 x 600
* expanded	
<b>Picture size</b>	376.3 x 301 mm
<b>Colors</b>	16.2 million
<b>Pixel Pitch</b>	0.294 mm
<b>Frequencies</b>	
Horizontal	31 - 81 kHz
Vertical	56 - 75 Hz
<b>Brightness (typical)</b>	300 cd/m <sup>2</sup>
<b>Contrast (typical)</b>	800:1
<b>Viewing angle (typical)</b>	
Horizontal	160°
Vertical	160°
<b>Response time (typical)</b>	5 ms
<b>Plug and Play</b>	VESA DDC2B
<b>Setting options</b>	
Brightness (Back light)	
Contrast, Volume control	
Picture position (horizontal and vertical)	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Activate factory settings	
Menu language	
<b>OSD Language</b>	
English, German, French, Italian, Spanish, Polish, Dutch, Russian	
<b>Base</b>	
Tilt angle	-5° / +20°
<b>Video input</b>	D-SUB, DVI-D
<b>Audio input / output</b>	
Audio signal input	3.5 mm stereo phone jack
Audio output	1 W (L) + 1 W (R)

<b>Electrical values</b> (internal power supply)	
Power draw	
EPA 'Standby':	0,4 W
EPA 'On Mode':	25 W
Max.	< 50 W
Rated voltage	100 - 240 V
Frequency	50 - 60 Hz
Protection class	1
<b>Temperatures/ dimensions/ weight</b>	
Ambient temperature (to IEC721):	
Working (recommended)	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D):	404 x 415 x 214 mm
(with Stand)	
Weight (Monitor only):	4.5 kg
<b>Reliability</b>	
MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight	50,000 h
(brightness > 50 % of original brightness)	
<b>Compliance with standards</b>	
Product safety	EN60950, NEMKO
Ergonomics	GS mark
	ISO13406-2
	(Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC
	(EN55022/B, EN55024, EN61000-3-2/-3);TCO 03; FCC Class B part 15
<b>Accessories</b>	
Power cable (1.8 m)*	For wall socket
	Euro-Schuko-Type CEE7
Plug type on Monitor	IEC-320-C13
Data cable (1.8 m)*	D-SUB (15-pin), DVI
Audio Cable (1.8m)*	3.5 mm stereo phone jack
* detachable on display	
<b>Special features</b>	Standardized mounting interface (according VESA FPMPI 100 mm)
	Integrated audio
	Kensington Lock
<b>Order code</b>	S26361-K1210-V381
<b>EAN</b>	433364 3414443